VERSION 2.3

Please note that the images are for illustrative purposes only.
The final product may vary in design, features or specifications.

CM30

CM30 is designed for workshop use. CM30 is manually operated and easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available.
Please also see product cards for other CM30/35 configurations.

TECHNICAL DATA	
Max. hose size (inch) [1]	2 / 1 ¼
Diameter (blade) external (mm)	300x3
Diameter (blade) internal (mm)	30
Max. hose OD (mm)	70
Exhaust outlet OD (mm)	60
Motor Power (kW) [2]	3.0/2.2
Motor Power (HP) [2]	4.0/2.9
Velocity, 50Hz (rpm)	2750
Velocity, 60Hz (rpm)	3370
DIMENSIONS (LxWxH)	
mm	600x503x739
inch	23.6x19.8x29.1
WEIGHT	
kg/lbs	42/92.4

Power supply cable not included.

1) Hydraulic hose, 1-2 wire / 4 wire
2) 3-phase / 1-phase

ABSOLUTE QUALITY MADE IN FINLAND

STANDARD FEATURES

Toothed blade (part no 12297)

OPTIONS

Smooth blade (part no 12319)



Toothed blade
as a standard feature.

Smooth blade
as an option.