



CM75QT is equipped with touch-control which enables

CM75QT is also available as SAFE-model.

connectivity and job queues.

TECHNICAL DATA		
Max. hose size (inch)	2	
Diameter (blade) external (mm)	520x4	
Diameter (blade) internal (mm)	38	
Max. hose OD (mm)	71	
Exhaust outlet OD (mm)	103	
Motor Power (kW/HP)	7.5 / 10.0	
Velocity, 50Hz (rpm)	2840	
Velocity, 60Hz (rpm)	2840	
DIMENSIONS (LxWxH) with 6m table		
mm	7134x1080x1330	
inch	280.8x42.5x52.3	
WEIGHT with 6m table		
kg/lbs	920/2024	



Toothed blade as a standard feature



Smooth blade as an option.

ABSOLUTE QUALITY AADE IN FINLAND

ı	STANDARD FEATURES		
ı	Touchscreen		
1	Toothed blade (part no 12251)		
1	Foot pedal		
П	Adjustable pneumatic pusher speed		
1	Adjustable hose support		
1	Measuring table (6 metre)		
ı	OPTIONS		
1	Measuring table (2 m segments) (part no 692091)		
1	Fume extractor (part no 691992)		
П	Smooth blade (part no 055201)		
1	Safeguard (SAFE-model)		
П	Motor brake (SAFE-model)		
1			
1			
1			
1			