



CM75QT

The most common problem in hose production is incorrect cutting length. Finn-Power CM75QT has been designed to solve that problem. CM75QT eliminates human mistakes.

CM75QT quality table has been equipped with automatic servo motor based measuring device with extreme accuracy.

Fast measuring reduces the cutting cycle time dramatically and enables fast return on investment.

CM75QT is equipped with touch-control which enables connectivity and job queues.

CM75QT is also available as SAFE-model.

ABSOLUTE
QUALITY
MADE IN
FINLAND

TECHNICAL DATA

| | |
|--------------------------------|------------|
| Max. hose size (inch) | 2 |
| Diameter (blade) external (mm) | 520x4 |
| Diameter (blade) internal (mm) | 38 |
| Max. hose OD (mm) | 71 |
| Exhaust outlet OD (mm) | 103 |
| Motor Power (kW/HP) | 7.5 / 10.0 |
| Velocity, 50Hz (rpm) | 2840 |
| Velocity, 60Hz (rpm) | 2840 |

DIMENSIONS (LxWxH) with 6m table

| | |
|------|-----------------|
| mm | 7134x1080x1330 |
| inch | 280.8x42.5x52.3 |

WEIGHT with 6m table

| | |
|--------|----------|
| kg/lbs | 920/2024 |
|--------|----------|



Toothed blade as a standard feature.



Smooth blade as an option.

STANDARD FEATURES

| |
|-----------------------------------|
| Touchscreen |
| Toothed blade (part no 12251) |
| Foot pedal |
| Adjustable pneumatic pusher speed |
| Adjustable hose support |
| Measuring table (6 metre) |

OPTIONS

| |
|---|
| Measuring table (2 m segments) (part no 692091) |
| Fume extractor (part no 691992) |
| Smooth blade (part no 055201) |
| Safeguard (SAFE-model) |
| Motor brake (SAFE-model) |
| Bar Code Reader BCR |